

SPECIFICATION

accompanying

Application for Grant of U.S. Letters Patent

INVENTOR: Ancil S. Taylor, Jr.  
P. O. Box 51118  
New Orleans, Louisiana 70151-1118

TITLE: "MAKE-UP WATER RE-CIRCULATION IN SLURRY  
PROCESSING UNIT"

BACKGROUND OF THE INVENTION

[0001] This invention relates generally to systems for processing waste materials, and more particularly to a system for treating sludge dredged from a waterway with an appropriate amount of water to be pumped in slurry form through a floating pipeline.

[0002] Much effort has been directed to cleaning up toxic wastes in a drive to restore our natural environment. Some of such toxic waste is in the form of sediment or sludge that lies at the bottom of waterways. These sediments tend to concentrate heavy-metal toxins, halogenated hydrocarbons, pesticides and anaerobic bacteria. Periodically, the sludge

0985767-062004

is removed by dredging and then transported, either by barge or pumped in slurry form through a floating pipeline, to an upland shore facility for disposal.

[0003] Conventional dredging processes generally include three operations: digging, transportation and disposal of the sludge. These processes employ either suction (e.g. hopper or cutter-head) or mechanical (e.g. dipper, ladder or clam shell) digging techniques. The dredgers alone, or with the aid of barges, floating pipelines and conveyors, are able to transport the dredged material to an on-shore site.

[0004] In the case of upland disposal, the sludge may be transported via a floating pipeline as a watery pulp or slurry. The concentration of sludge solids is very low; the ratio by weight between the sludge and water is from about 1/7 to about 1/15, or one part of sludge solids to every 7 to 15 parts of water. At the disposal site, the sludge solids are separated from the water and the water is returned to the waterway as an effluent. Because some contaminated sludge remains in the returned water, pollution of the water environment is very likely.

[0005] The Hazardous and Solid Waste Amendments (HSWA)







cutting the density and viscosity to the desired parameters was supplied by clear water pumped from the surrounding waterway into the dredge's sea chest in the barge. While the present invention optionally allows some make-up water to be sourced from overboard, the ability to re-cycle process water from the on-shore disposal facility to meet the make-up water needs of the SPU provides an improved solids-to-water ratio by avoiding the introduction of any new clear water from overboard during the slurry preparation phase.

[0013] Process treatment water is returned from the on-shore disposal facility to be used as make-up water on the dredge by a supply pipeline that is floated alongside the slurry delivery pipeline that transports slurry from the dredge to the disposal facility. The process treatment water is pressurized by a centrifugal pump located at the at the CDF and then boosted by a high pressure pump to the desired working pressure once aboard the dredge. Some of the process water is discharged as needed directly into the dredge hopper for initial sludge dilution and some of it is injected as make-up water into the slurry at one or more specific gravity measurement stations on board the dredge.

[0014] Such pump control together with multiple

specific gravity measurements and make-up water injection between measurement stations provides an accurate indication of the amount of make-up water to be injected, even though the sludge solids are of varying composition. Inlet slurry flow, inlet make-up water flow, the slurry discharge flow, the make-up water pressure and the pressure in the slurry delivery pipeline can all be controlled using a primary fixed speed inlet pump, a booster pump for the make-up (process treatment) water and a variable speed discharge pump together with throttling valves in the make-up water injection pipes. This minimizes cost and avoids maintenance problems that would be caused by throttling valves in the slurry piping.

**[0015]** In the preferred embodiment, the slurry processing unit includes an inlet make-up water booster pump and an inlet slurry pump, with the inlet slurry pump being operated at a constant pumping rate, and with flow of the inlet slurry pump not being throttled; inlet water piping connecting the make-up water pipeline to the dredge hopper and to the inlet of the booster pump; a speed-controlled slurry discharge pump; slurry piping connecting the output of the inlet slurry pump to the input of the discharge pump; discharge piping connected between an outlet of the discharge pump and the floating pipeline; make-up water piping having an

input connected to the output of the inlet make-up water pump, and having a make-up water injection pipe connected to an intermediate point of the slurry piping.

[0016] Generally, the invention is a closed loop slurry processing system for pumping varying compositions of slurry via a floating delivery pipeline to an on-shore treatment facility, a floating return pipeline connecting the on-shore treatment facility for supplying process treatment water as make-up water to the input of a slurry processing unit including an inlet make-up water booster pump and an inlet slurry pump; a discharge pump; slurry piping connecting the output of the inlet slurry pump to the input of the discharge pump; discharge piping connected between an outlet of the discharge pump and the floating slurry pipeline; and a low pressure pump coupled between the on-shore treatment facility and the return pipeline for supplying process treatment water that has been separated from the slurry solids to be used for initial sludge dilution in the dredge hopper and for specific gravity adjustment in one or more make-up water injection stations within the slurry processing unit.

[0017] This invention also provides a method for controlling a slurry processing unit for pumping varying



compositions of slurry through a floating delivery pipeline, with the unit having slurry piping connecting the output of an inlet slurry pump to the input of a discharge pump and with discharge piping connected between an outlet of the discharge pump and the floating delivery pipeline. The method includes the steps: pumping slurry through a floating pipeline to an on-shore treatment facility; separating solids from the slurry; supplying make-up water derived from the on-shore treatment facility through a floating return pipeline to a booster pump, injecting make-up water from the booster pump into the slurry processing unit through make-up water piping and supplying make-up water delivered by the return pipeline into the dredge hopper for initial dilution of the sludge.

#### BRIEF DESCRIPTION OF THE DRAWING

[0018] This invention can be best understood by reference to the following drawing figures in which:

[0019] FIGURE 1 shows a dredge, barge-mounted slurry processing unit, a floating delivery pipeline to an on-shore slurry separation/treatment facility, and a floating return pipeline for returning process treatment water to the slurry processing unit;

[0020]           FIGURE 2 is a plan view of a slurry processing unit mounted on a barge;

[0021]           FIGURE 3 shows the barge-mounted slurry processing unit in elevation; and,

[0022]           FIGURE 4 shows a schematic slurry piping and process flow diagram.

#### DETAILED DESCRIPTION OF THE INVENTION

[0023]           Referring now to FIGURE 1 - FIGURE 4, a slurry processing unit 10 is mounted on a dredging barge 12 which transfers slurry through a floating delivery pipeline 14 to an on-shore treatment facility 16. Toxic sludge 18, for example creosote sludge, is dredged from the bottom of a river 20. The toxic sludge 18 is loaded into a sump or hopper 22 by means of a power loader 24. The hopper 22 is shown in FIGURE 2 and FIGURE 3. Make-up water is derived from process treatment water W pumped from the on-shore facility 16 via a floating supply pipeline 25 into the hopper 22 and is mixed with the raw dredge material to produce a pumpable, raw slurry.

[0024]           Referring now to FIGURE 2, the slurry

processing unit 10 includes an inlet slurry pump 26 and slurry piping 28. Also shown is an inlet make-up water booster pump 30 and a slurry discharge pump 32. The discharge pump 32 is speed controlled. The slurry piping 28 connects the output 34 of the inlet slurry pump 26 to the input 36 of the discharge pump 32. In addition, discharge piping 38 connects between the outlet 40 of the discharge pump 32 and the floating delivery pipeline 14 (FIGURE 1). Specific gravity sensor pairs 42, 44 and 46, 48 and 50, 52 are located at spaced locations along the slurry piping sections 28A, 28B and 28C, respectively. The sensor units of each pair provide analog signals that are combined to produce a specific gravity value that is characteristic of the slurry flowing through the slurry piping section extending between the sensor units of each sensor pair.. Also shown are flow sensors 54, 56 and 58 connected between the slurry piping sections. FIGURE 3 shows an elevation view of the pumping barge and the relationship between power loader 24 and the hopper 22.

**[0025]** FIGURE 4 shows the injection of make-up water W into the slurry piping 28 between the adjoining piping sections 28A, 28B and 28B, 28C and the terminal section 28D. In particular, the make-up water piping has a manifold 60 with an inlet port 62 connected to the output 64 of the inlet make-

up water pump 30 and has multiple make-up water outputs, including a first make-up water injection pipe 66 connected to the slurry piping section 28B between the second and third specific gravity sensors 44, 46, and a second make-up water injection pipe 68 connected to the slurry piping section 28C between the third and fourth specific gravity sensors 48, 50.

**[0026]** The first flow sensor 54 is connected in the slurry piping between the first piping section 28A and second piping section 28B, and between the second and third specific gravity sensors 44, 46. The second flow sensor 56 is connected in the slurry piping between the fourth specific gravity sensor 48 and the fifth specific gravity sensor 50. The third flow sensor 58 is connected in the terminal piping section 28D between the sixth specific gravity sensor 52 and the inlet port 36 of the slurry discharge pump 32.

**[0027]** A controller 70 receives analog specific gravity signals 72, 74, 76 from the specific gravity sensors 42, 44, 46, 48, 50 and 52, respectively and analog flow signals 78, 80 and 82 from the flow sensors 54, 56 and 58, respectively. A first controllable throttle valve 84 is connected in the first make-up water injection pipe 66. A second controllable throttle valve 86 is in the second make-up



accurate determination of appropriate total make-up water addition to be made.

[0030]           The specific gravity sensor pairs 42, 44; 46, 48; and 50, 52 include pressure sensors located at first and second elevations in the substantially vertical sections 28A, 28B and 28C of slurry piping. While the slurry processing unit preferably is constructed as described above, the make-up water piping may be operated without the controllable throttle valve and especially without the third controllable throttle valve 88 and the third make-up water injection pipe 90.

[0031]           An auxiliary make-up water line 102 connected in the main slurry inlet conduit 104 can also be used to introduce make-up water into the hopper 22 for initial dilution, or can be used to aid in flushing the system, with shutoff valve 106 only opened during cleaning.

[0032]           It will be understood that the slurry processing system 10 can be controlled using a variable speed drive 100 to control the pumping rate of the output pump 32. In particular, for example, the flow of the inlet slurry pump 26 can be controlled by throttling the make-up water injection and by speed controlling the discharge pump 32 even though the

inlet slurry flow is not controlled or throttled.

**[0033]** Referring again to Figure 1 and Figure 4, the on-shore processing facility 16 is connected in a closed loop with the barge-mounted slurry processing unit 12 by the slurry delivery pipeline 14 and the make-up water return pipeline 25. Pressurized slurry 108 is sprayed into a containment vessel 110 through a delivery manifold 112. In the containment vessel, the sludge slurry is treated with chemical decontamination reagents C that are sprayed into the containment vessel through a spray nozzle assembly 114. Additional treatment reagent/additives or any other desired ingredients may also be added through the spray nozzle assembly.

**[0034]** In the containment vessel, the sludge solids S are skimmed off from the main compartment of the vessel into an adjoining collector compartment and are introduced for treatment in the next stage. The aqueous phase which includes the make-up water and the treatment chemicals, designated W, is separated and removed through drain lines 116, 118 and input into a low pressure pump 120 that has an output connected to the make-up water recovery pipeline 25. According to this arrangement, the make-up water is derived

from the aqueous phase W after it has been separated from the chemically-treated sludge solids at the on-shore facility 16.

[0035] The aqueous phase W from which the make-up water is derived is transported via the buoyant pipeline 25 to the inlet of the booster pump 30, as shown in Figure 4, where it is boosted to the pressure level necessary to accommodate the make-up water needs of the slurry processing unit 12. Some of the process water W is injected as make-up water through the injection piping 66,68,90 into the pressurized slurry flow stream at one or more specific gravity measurement stations on board the dredge as previously described. Some of the returned process water W is discharged directly into the dredge hopper 22 through a flow line 122 for initial dilution of the sludge. The amount of dilution flow is regulated by the controller 70 via a throttle signal 124 and throttle valve 126.

[0036] The closed loop recycling process described above has reduced the amount of clear make-up water added to the processing system by more than 50%. This has resulted in a substantial reduction in the overall cost of remediation by reducing the amount of treatment water that must be cleaned prior to its release from the contaminated dredging operation.



